
PHOENIX
TAPWARE, SHOWERS & ACCESSORIES

INSTALLATION INSTRUCTIONS
WALL SET ON PLATE
IN0218 REV D

NOTE
Check the rubber seal under each spindle:


HOT ←RED

COLD ←BLUE




BREACH SET-UP

- Ensure that seats in the Breach are in good condition and are free of foreign objects.
- The recommended installation range for the breach are as shown:
- Reseat if required.
- Recess Breaches must be 100mm each side of the Threaded Elbow



2

Fix Back Plate to wall using the adhesive tape on the back.




3

Firmly screw Spindle into the Breach.

DO NOT OVERTIGHTEN

Fit Fibre Washer around the Spindle and then firmly fasten the Bonnet onto the Spindle using a spanner.




4

Fit O-Ring to the groove in the rear of the Flange.

Firmly fasten Flange onto the Spindle.

Fit Handle Hub to Spindle and fasten with the Grub Screw using the Allen Key provided.


Screw the Handle Pin into the Handle Hub



5

Apply Teflon Tap to Threaded Elbow.

Screw Outlet onto Threaded Elbow.



recommended working pressure
150-500 KPa
maximum hot water temperature
75 degrees

NOTE:
- If the pressure exceeds or is likely to exceed 550kpa, an approved pressure limiting device must be installed.
- Flush out all pipe work prior to installation.
- If the water temperature exceeds 75°C, an approved tempering valve must be fitted.
- Installation should comply with Australian standard AS3500.1 or relevant local authority requirements.

Showers may not be suitable for use within:
• Gravity-fed water systems
• Some instantaneous hot water systems; or
• Pressure supply less than 150kPa;

NOTE: The 500kPa maximum water supply pressure does not apply to fire service outlets.

Failure to comply with the above may void all warranties.

WARRANTY:
Please refer to the full warranty statement enclosed with the product before installing. Or visit www.phoenixtapware.com.au to download a copy.

MAINTENANCE AND CARE:
- Products should be cleaned with mild liquid detergent or soap and water.
- Do not use cream cleaners or citrus based cleaning products, as they are abrasive.
- Use of unsuitable cleaning agents may damage the surface. Any damage caused in this way will not be covered by warranty.

DISCLAIMER:
While we aim to ensure the specifications shown are correct at the time of printing, Phoenix Tapware reserves the right to make modifications without prior notice. Always use the physical product measurements for mark-ups and roughing-in as the line drawing shown may differ from the actual product over time.

*All measurements are shown in millimeters.

(03) 9780 4200
www.phoenixtapware.com.au